



Patchcable RJ45 CAT.6 S-STP



Product features

- PiMF 500 MHz, with Hirose TM21 connector
- Halogen-free
- Configuration accordance to TIA/EIA 568B
- Colour: grey (also available in other colours)

Approvals (Norm references)



Part number	Article designation	Colour	Length in m	PU
S-STP Patchcable CAT.6				
CE6847	Patchcable RJ45 CAT.6 S-STP 0.5m	grey	0.5	5 pieces
CE6848	Patchcable RJ45 CAT.6 S-STP 1.0m	grey	1.0	5 pieces
CE6849	Patchcable RJ45 CAT.6 S-STP 1.5m	grey	1.5	5 pieces
CE6850	Patchcable RJ45 CAT.6 S-STP 2.0m	grey	2.0	5 pieces
CE6851	Patchcable RJ45 CAT.6 S-STP 3.0m	grey	3.0	5 pieces
CE6852	Patchcable RJ45 CAT.6 S-STP 5.0m	grey	5.0	5 pieces
CE6853	Patchcable RJ45 CAT.6 S-STP 7.5m	grey	7.5	5 pieces
CE6854	Patchcable RJ45 CAT.6 S-STP 10.0m	grey	10.0	5 pieces
CE6855	Patchcable RJ45 CAT.6 S-STP 15.0m	grey	15.0	1 piece
CE6856	Patchcable RJ45 CAT.6 S-STP 20.0m	grey	20.0	1 piece

Also further different-coloured versions available.

LANmark-6 RJ45 Patchcord



Product features

- The Patchcord fully corresponding to category 6 maximises the channel performance and exceeds the requirements of ISO/IEC 11801:2002 as part of a LANmark-6 wiring of Class E. This offers an improved data transmission rates and enables the inclusion of consolidation points for maximum system flexibility.
- Halogen free, flame-retardant sheath with less release of smoke gases than standard
- Screened version

Approvals (Norm references)



Part number	Article designation	Colour	Length in m	PU
LANmark-6 RJ45 Patchcord				
CE6147	LANmark-6 RJ45 Patchcord 0.5m	orange	0.5	1 piece
CE6148	LANmark-6 RJ45 Patchcord 1.0m	orange	1.0	1 piece
CE6149	LANmark-6 RJ45 Patchcord 1.5m	orange	1.5	1 piece
CE6150	LANmark-6 RJ45 Patchcord 2.0m	orange	2.0	1 piece
CE6151	LANmark-6 RJ45 Patchcord 3.0m	orange	3.0	1 piece
CE6152	LANmark-6 RJ45 Patchcord 5.0m	orange	5.0	1 piece
CE6154	LANmark-6 RJ45 Patchcord 10.0m	orange	10.0	1 piece
CE6155	LANmark-6 RJ45 Patchcord 15.0m	orange	15.0	1 piece

LANmark-7 GG45 Patchcord



Product features

- The LANmark-7 Patchcable with two four-paired, non-switched CAT.7 connectors makes it possible to operate one GG45 Permanent Link in 600 MHz mode.
- Screened version
- 2x GG45 4-pair, not downward compatible plug
- Halogen free, low smoke zero halogen (LSZH)

Approvals (Norm references)



Part number	Article designation	Colour	Length in m	PU
LANmark-7 RJ45 Patchcord GG45				
60641	LANmark-7 GG45 Patchcord 1.0m	orange	1.0	1 piece
60642	LANmark-7 GG45 Patchcord 2.0m	orange	2.0	1 piece
60643	LANmark-7 GG45 Patchcord 3.0m	orange	3.0	1 piece
60644	LANmark-7 GG45 Patchcord 5.0m	orange	5.0	1 piece
60645	LANmark-7 GG45 Patchcord 10.0m	orange	10.0	1 piece